



**FLAME RETARDANT
ZERO HALOGEN
BUILDING WIRE**



PASAKA®

FRZH BUILDING WIRES

ISO |  | CE

PASAKA FRZH (FLAME RETARDANT ZERO HALOGEN) BUILDING WIRE

These wires are insulated with non-toxic EVA based Flame Retardant Halogen Free compound to out-perform all other insulation on toxicity parameters by generating almost zero toxic gases in case of fire. The small amount of smoke that is generated is white and of low density (20%). Thus, fire fighting and evacuation of casualties is easy.

These eco-friendly wires are a class of its own and are the ultimate in the Building Wires. Made of multi strand copper conductors accurately drawn in imported fine wire drawing machines and annealed on-line, they offer uniform resistance. They are recommended to be used where large congregation of people is expected. Typical applications are in Hotels, Theatres, Multiplexes, Shopping Malls, Metro Railways, Hospitals, Schools, Commercial Complexes and high-rise residential buildings.

FIRE-EFFECT & SMOKE EMISSION COMPARISON TEST



Ordinary PVC Wires
Prone to catch flame, burns with lot of black smoke and toxic gases.



FRLS Wires
Delays fire action, burns slowly with less smoke.



FRZH Wires
Highly fire-resistant, burns with no flame and negligible non-toxic smoke.

UNIQUE FEATURES OF OUR PROCESS

- On-line wire drawing and annealing.
- High speed extruders (upto 500 metres per minute).
- FRZH insulated for better insulation & electrical properties.
- Automatic on-line critical diameter control.
- Stringent quality control.

1100V

SINGLE CORE, FRZH INSULATED WIRES IN VOLTAGE GRADE 1100 V.

Nominal area of Conductor	Number/Nom. Dia. of wire	Thickness of Insulation (Nom.)	Approx. overall Diameter	Current carrying capacity* Rating	Resistance (Max.) per Km. @ 20°C
Sq. mm.	mm.	mm.	mm.	Amps.	Ohms
1.0	14/0.3	0.7	2.65	12	18.10
1.5	22/0.3	0.7	2.95	16	12.10
2.5	36/0.3	0.8	3.55	22	7.41
4.0	56/0.3	0.8	4.0	29	4.95
6.0	84/0.3	0.8	4.6	37	3.30
10.0	80/0.4	1.0	5.8	51	1.91
16.0	126/0.4	1.0	6.8	68	1.21

Standard Colours : Red, Yellow, Blue, Black and Green (for earthing).
Supplied in 90 metre lengths in attractive cartons.

* As per IS 3961 (PartV)-1968

THE ABOVE DATA IS INDICATIVE AND MAY BE REVISED WITHOUT PRIOR INFORMATION.
PASAKAWILL NOT BE LIABLE FOR ANY DAMAGES ARISING OUT OF INCORRECT APPLICATION.